

The 4Front® 2 HD is the next generation of the 4Front® Power Chair but is heavy duty! New Smart Traction Control (STC), along with Smooth Ride Suspension (SRS), provide stability for smooth obstacle transitions and unmatched driving performance. Additional new features include 4-pole motors and more robust caster arms.







# Specifications

opeomoditeme	
DRIVE WHEELS	Standard: 14" flat free Optional: 14" knobby 14" pneumatic
CASTER WHEELS	Rear: 9" flat free
ANTI-TIP WHEELS	Front: 4" flat free
MAXIMUM SPEED <sup>1</sup>	Up to 5 mph (2.7 mph when elevated)
GROUND CLEARANCE	3.14" (battery tray)
TURNING RADIUS <sup>2</sup>	25.9"
OVERALL LENGTH <sup>2</sup>	39.9"
BASE WIDTH	24"
SEATING SIZES	
TRU-Balance® 3 HD Static Seat	Width: 20-24" Depth: 20-24"
TRU-Balance® 3 HD Power Tilt	Width: 20-24" Depth: 20-22"
TRU-Balance® 3 Power Lift & Tilt	Width: 20-24" Depth: 20-24"
SEAT-TO-FLOOR HEIGHTS	
TRU-Balance® 3 HD Static Seat <sup>5</sup>	15-17" (not available with Synergy®)
TRU-Balance® 3 HD Power Tilt <sup>5</sup>	17.75-19.75"
TRU-Balance® 3 Power Lift & Tilt <sup>5</sup>	17.75-19.75"
BATTERY SIZE <sup>3</sup>	Group 24
BATTERY WEIGHT <sup>7</sup>	Group 24: 51.5 lbs. each
AVAILABLE ELECTRONICS 8	120A Q-Logic 3
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	4-pole
WEIGHT CAPACITY <sup>4</sup>	Up to 450 lbs. Up to 400 lbs. with 10" seat lift
BASE WEIGHT	130 lbs.
MEDICARE CODE COVERAGE	Group 3: Solid Seat Pan HD (K0850) Single Power HD (K0858) Multiple Power HD (K0862)

- 1) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
- Without front riggings
  Battery capacity may change when adding power positioning systems.
- 4) Weight capacity is dictated by the selection of seating.
- 5) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- 6) Battery weight may vary +/- 3 lbs. based on manufacturer.
- 7) All Quantum Rehab® units can be ordered with specialty controls.
- 8) Call for availability
- 9) Seat-to-floor heights are measured with the unit unloaded. Due to the 4Front 2 HD's suspension system, seat-to-floor heights are approximately 0.25" lower when the unit is loaded.

Quantum Rehab® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.


### Standard Features

- · 4-pole motors
- NEW Smart Traction Control (STC)
- Superior, automotive-grade SRS (Smooth Ride Suspension)
- · Unmatched driving performance and ride quality
- · Advanced stability for smooth obstacle transitions
- · More robust caster arms
- · Q-Logic 3e controller
- Speeds up to 5 mph
- · LED front and rear fender lights
- · Quiet ride technology

## **Options**

- 10" of power adjustable safe seat elevation at speeds of up to 2.7 mph
- Trilogy vent tray 8
- Compact vent tray 8
- · Quantum® backup camera

#### Colors



## Hydrographics





Military Digital Camo

Faded Glory



