

REHAB POWER CHAIR SOLUTIONS



Q6 EDGE®
shown in *Viper Blue*
with TRU-Balance® 3
Power Positioning

Q6 edge®

With features like standard 4-pole motors, Mid-Wheel 6® drive design and ATX Suspension, the Q6 Edge® is engineered to meet the performance needs of the most active user. The Q6 Edge accepts a complete range of seating and electronics options to deliver exceptional rehab capability at an excellent value.

QUANTUM®

Specifications

DRIVE WHEELS	Standard: 14" Solid Optional: 14" Pneumatic 14" Knobby
CASTER WHEELS	Front: 6" Solid Rear: 6" Solid
ANTI-TIP WHEELS	N/A
MAXIMUM SPEED ⁴	Up to 5 mph (Optional: 6 mph)
GROUND CLEARANCE	3" (frame center)
TURNING RADIUS ⁵	20"
OVERALL LENGTH	35.5" without foot riggings
BASE WIDTH	24"
SEATING SIZES	
Synergy[®]/Static Seat	Width: 10-22" Depth: 10-22"
TRU-Balance[®] 3 Power Tilt	Width: 12-22" Depth: 12-22"
TRU-Balance[®] 3 Lift & Tilt	Width: 12-22" Depth: 12-22"
SEAT-TO-FLOOR HEIGHTS	
Synergy[®]/Static Seat ⁸	16.5-18.5"
TRU-Balance[®] 3 Power Tilt ⁸	17.5-19.5"
TRU-Balance[®] 3 Lift & Tilt ⁸	18-20"
MANUAL TILT/RECLINE ¹⁰	Yes
BATTERY SIZE ⁶	NF-22
BATTERY WEIGHT ¹⁴	38 lbs.
AVAILABLE ELECTRONICS ¹²	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	4-Pole 5 mph ¹ or 6 mph ²
WEIGHT CAPACITY ⁷	300 lbs.
BASE WEIGHT	138 lbs.
MEDICARE CODE COVERAGE	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)

- 1) Standard
- 2) Optional
- 3) Requires HD Suspension
- 4) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
- 5) Without front riggings
- 6) Battery capacity may change when adding power positioning systems.
- 7) Weight capacity is dictated by the selection of seating.
- 8) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- 9) 250 lbs. weight capacity with TRU-Balance[®] Systems
- 10) The Synergy[®] Manual Tilt weight capacity is 75 lbs. and maximum dimensions are 14" W x 14" D. Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
- 11) Requires Group 34 batteries
- 12) All Quantum Rehab[®] units can be ordered with specialty controls
- 13) Required with high-speed motors
- 14) Battery weight may vary +/- 3 lbs. based on manufacturer.

Features

- Mid-Wheel 6[®] allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance[®] 3 Power Positioning
- Low impact OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- ATX Suspension (Active-Trac[®] with extra stability) incorporates front OMNI-Casters and semi-independent rear caster beam for enhanced performance over more varied terrain

Options

- TRU-Balance[®] 3 Lift & Tilt
- TRU-Comfort 2 Seating System
- Q-Logic 2 EX Drive Controls
- 6 mph motor package
- Accu-Trac Advanced Tracking Technology
- TRU-Balance[®] 3 (10") Lift Trilog vent tray
- Compact vent tray
- LED full lighting package
- 4" wide flat-free knobby extended traction tires
- WC19 transit securement package

Colors

