



AVAILABLE WITH 12" iLEVEL® AT 4.5 MPH



AVAILABLE WITH 12" iLEVEL®



AVAILABLE WITH 10" ELEVATION



AVAILABLE WITH 12" iLEVEL®



AVAILABLE WITH 12" iLEVEL®



ALSO AVAILABLE: KOZMO® PORTABLE



AVAILABLE WITH 10" HD iLEVEL®



	EDGE 3	Q6 EDGE® 2.0	4FRONT®	Q6 EDGE® 2.0X	Q6 EDGE® Z	KOZMO®	Q6 EDGE® HD	QUANTUM® RIVAL®	J6	QUANTUM® 1450
DRIVE CONFIGURATION	Mid-wheel Drive	Mid-wheel Drive	Front-wheel Drive	Mid-wheel Drive	Mid-wheel Drive	Rear-wheel Drive	Mid-wheel Drive	Rear-wheel Drive	Mid-wheel Drive	Front-wheel Drive
DRIVE WHEELS	14" Solid Optional: 14" Pneumatic	14" Solid Optional: 14" Pneumatic; 14" Knobby	14" Flat Free Optional: 14" Knobby	14" Solid Optional: 14" Pneumatic; 14" Knobby	14" Run Flat Optional: 14" Pneumatic; 14" Knobby	9" Solid	14" Run Flat Optional: 14" Pneumatic; 14" Knobby	14" Solid Optional: 14" Pneumatic; 14" Knobby	10" Solid Optional: 10" Pneumatic	14" Solid
CASTER WHEELS	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid (Optional: 8") Rear: 6" Solid (Optional: 8")	Rear: 9" Flat Free	Front: 6" Solid (Optional: 8") Rear: 6" Solid (Optional: 8")	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 9" Pneumatic	Front: 5" Solid Rear: 6" Solid	9" Solid
ANTI-TIP WHEELS	N/A	N/A	Front: 4"	N/A	N/A	3" Solid	N/A	N/A	N/A	4" Solid
MAXIMUM SPEED ⁴	Up to 6 mph (4.5 mph w/iLevel)	Up to 6 mph	Up to 6 mph	Up to 6 mph	Up to 6 mph (Optional: 8 mph) ¹³	Up to 3.6 mph	Up to 4.7 mph	Up to 6 mph (Optional: 8 mph)	Up to 4 mph	Up to 4.5 mph
GROUND CLEARANCE	2.7" (battery tray)	2.7" (battery tray)	3" (motor pivot)	2.7" (battery tray)	3" (frame base)	1.6" at anti-tip bracket	3" (frame center)	3.25" (frame base)	2.5" (frame)	1.5" (anti-tip wheels)
TURNING RADIUS ⁵	20.5"	6" casters: 20.5" 8" casters: 23.25"	24.5"	6" casters: 20.5" 8" casters: 23.25"	19.75"	25.45" with foot platform	19.75"	35.75"	22"	26.5"
OVERALL LENGTH ¹¹	32.23" without foot riggings	6" casters: 32.23" 8" casters: 40.48"	40"	6" casters: 35.5" 8" casters: 40.48"	35.6"	33.09" with foot platform	35.6"	36"	34.74"	38.25"
BASE WIDTH	24.4"	24.4"	24"	24.4"	26.25"	22.6"	26.25"	25"	23.19"	29.25"
Seating Sizes:										
SYNERGY®	N/A	W: 10-22" D: 10-22"	N/A	W: 10-22" D: 10-22"	W: 10-24" D: 10-24"	N/A	W: 20-32" D: 20-28"	W: 12-22" D: 12-22"	W: 10-20" D: 10-20"	W: 20-32" D: 20-28"
TRU-BALANCE® 3 STATIC	W: 10-22" D: 10-22"	W: 10-22" D: 10-22"	W: 12-22" D: 12-22"	W: 10-22" D: 10-22"	W: 12-24" D: 12-24"	N/A	N/A	W: 12-22" D: 12-22"	W: 10-20" D: 10-20"	N/A
TRU-BALANCE® 3 POWER TILT	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-24" D: 14-24"	N/A	N/A	W: 12-22" ³ D: 12-22" ³	W: 14-20" D: 14-20"	N/A
TRU-BALANCE® 3 LIFT & TILT	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 16-22" D: 14-22"	W: 12-24" D: 12-24"	N/A	N/A	W: 12-22" ³ D: 12-22" ³	N/A	N/A
TRU-BALANCE® 3 HD STATIC	N/A	N/A	N/A	N/A	N/A	N/A	N/A	W: 20-32" D: 20-28"	N/A	N/A
TRU-BALANCE® 3 HD POWER TILT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	W: 20-32" D: 20-25"	N/A	N/A
TRU-BALANCE® 3 HD LIFT & TILT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	W: 20-24" D: 20-25" ¹⁰	N/A	N/A
TRU-BALANCE® 2 HD STATIC	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	W: 20-32" D: 20-28"
TRU-BALANCE® 2 HD POWER TILT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	W: 20-32" D: 20-28"
TRU-BALANCE® FLEX SEAT	W: 15-22" D: 15-20"	W: 15-22" D: 15-20"	N/A	N/A	N/A	N/A	N/A	W: 15-22" D: 15-20"	N/A	N/A
KOZMO™ PEDIATRIC STATIC SEAT	N/A	N/A	N/A	N/A	N/A	W: 12-16" D: 12-16"	N/A	N/A	N/A	N/A
Seat-to-Floor Heights^{16,17}:										
SYNERGY® / STATIC ⁸	16.5" - 18.5"	16.5-18.5"	15.25-17.25" <small>NOT AVAILABLE WITH SYNERGY®</small>	16.5-18.5"	16.5"-18.5"	N/A	17.5-19.5"	16.5-18.1"	Synergy®: 15.75-17.5"; Static: 16.75"	16.5-18.5"
POWER TILT ⁸	17.5" - 19.5"	17.5-19.5"	17.5-19.5"	17.5-19.5"	18.5"-20.5"	N/A	18.5-20.5"	18-19.6"	16.75"	18.125-20.125"
LIFT & TILT ⁸	17.5" - 19.5"	17.5-19.5"	17.75-19.75"	17.5"-19.5"	18.5"-20.5"	N/A	17.75-19.75"	18.5-20.1"	N/A	N/A
TRU-BALANCE® FLEX SEAT ⁸	16.5" - 19.5"	16.5-19.5"	N/A	N/A	N/A	N/A	N/A	16.5-18.1"	N/A	N/A
KOZMO™ PEDIATRIC STATIC SEAT ⁸	N/A	N/A	N/A	N/A	N/A	15.75"-16.75"	N/A	N/A	N/A	N/A
MANUAL RECLINE	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No
BATTERY SIZE ⁶	NF-22 (2)	NF-22	Group 24: 51.5 lbs. Group 34: 38.5 lbs.	NF-22	Group 24	(2) 18A, 12 V, deep cycle	Group 24	Group 24	U-1	Group 24
BATTERY WEIGHT ¹⁴	38 lbs. each	38 lbs.	51.5 lbs.	38 lbs.	52 lbs. each	31 lbs.	52 lbs.	52 lbs.	23.4 lbs.	52 lbs.
AVAILABLE ELECTRONICS ¹²	120A Q-Logic 3 EX 75A Q-Logic 2 NE 75A Q-Logic 2 NE+	120A Q-Logic 3 EX 75A Q-Logic 2 NE 75A Q-Logic 2 NE+	120A Q-Logic 3 EX	120A Q-Logic 3 EX	75A Q-Logic 2 NE+ 100A Q-Logic 2 EX	40A, PG GC3 (non-programmable)	120A Q-Logic 3 EX 75A Q-Logic 2 NE 75A Q-Logic 2 NE+	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX	70A Q-Logic 2 NE 70A Q-Logic 2 NE+ 70A Q-Logic 2 EX	90A VR2 6-key 100A Q-Logic 2 EX
BATTERY CHARGER	8A Off-board	8A Off-board	8A Off-board	8A Off-board	8A Off-board	3.5A Off-board	8A Off-board	8A Off-board	5A Off-board	8A Off-board
MOTOR PACKAGES	2-Pole Mid-Wheel 6®	2-Pole Mid-Wheel 6®	2-pole, front-wheel drive	2-Pole Mid-Wheel 6®	4-Pole Mid-Wheel 6®	N/A	4-Pole 4.7 mph ¹	4-Pole 6 mph ¹ or 4-Pole 8 mph ²	2-Pole 4 mph	4-Pole 4.5 mph
WEIGHT CAPACITY ⁷	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	200 lbs.	450 lbs. ¹⁵	300 lbs.	300 lbs. ⁹	600 lbs.
BASE WEIGHT	138.6 lbs.	138.6 lbs. (6" casters) 148 lbs. (8" casters)	140 lbs.	138.6 lbs. (6" casters) 148 lbs. (8" casters)	143.5 lbs.	67 lbs.	143.5 lbs.	129 lbs.	100.2 lbs.	195 lbs.
MEDICARE CODE COVERAGE - For more information on Medicare code coverage, please consult our Product Planning and Reimbursement Center.										
	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	KOZMO®: Group 2: Standard (K0822) KOZMO® PORTABLE: Group 2: Standard (K0820)	Group 3: Heavy Duty (K0850/K0851), Single Power HD (K0858), Multiple Power HD (K0862)	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	Group 2: Standard (K0822/K0823), Single Power (K0835)	Group 3: Very Heavy Duty (K0852/K0853), Single Power Very HD (K0860),

1) Standard
2) Optional
3) Requires HD Suspension
4) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
5) Without front riggings
6) Battery capacity may change when adding power positioning systems.

7) Weight capacity is dictated by the selection of seating.
8) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Depths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
9) 250 lbs. weight capacity with TRU-Balance® Systems
10) A minimum seating size of 20" x 20" is required with iLevel® on the Q6 Edge® HD; maximum seating size is 24" x 25"

11) Without foot riggings
12) All Quantum units can be ordered with specialty controls
13) iLevel® not available with 8 mph motor package
14) Battery weight may vary +/- 3 lbs. based on manufacturer.
15) Weight capacity is reduced to 400 lbs. with iLevel® power adjustable seat height

16) Seat-to-floor heights are measured with the unit unloaded. Due to the 4Front's suspension system, seat-to-floor heights are approximately 0.25" lower when the unit is loaded.
17) 16.5" seat-to-floor height is not available with power tilt or iLevel®. 19.5" seat-to-floor height is not available with static seat or power recline.

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement. The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice.